



Parker Hannifin Corporation - Sporlan Division
206 Lange Drive
Washington, MO, U.S.A., 63090
Telephone: (636) 239 1111

Dual Purpose Vacuum Pump Oil

L339; L340; L341

SDS Revision Date (mm/dd/yyyy): 02/08/2019

Page 1 of 10

SAFETY DATA SHEET

SECTION 1. IDENTIFICATION

Product identifier used on the label

: **Dual Purpose Vacuum Pump Oil**

Product Code(s) : L339 (P/N 475352); L340 (P/N 475353); L341 (P/N 475354)

Recommended use of the chemical and restrictions on use

: Hydraulic oil
Restriction on use: None known

Chemical family : Mixture.

Name, address, and telephone number
of the supplier:

Parker Hannifin Corporation - Sporlan Division

206 Lange Drive
Washington, MO, U.S.A.
63090

Supplier's Telephone # : (636) 239-1111

24 Hr. Emergency Tel # : Chemtrec 1-800-424-9300 (Within Continental U.S.); Chemtrec 703-527-3887
(Outside U.S.).

Name, address, and telephone number of
the manufacturer:

Refer to supplier

SECTION 2. HAZARDS IDENTIFICATION

Classification of the chemical

Clear amber liquid. Petroleum odor.

This material is not classified as hazardous under U.S. OSHA regulations (29CFR 1910.1200) (Hazcom 2012) and Canadian WHMIS regulations (Hazardous Products Regulations) (WHMIS 2015).

Label elements

Hazard pictogram(s)

None required under U.S. OSHA Hazcom 2012 and Canadian WHMIS 2015 regulations.

Signal Word

None required.

Hazard statement(s)

None required.

Precautionary statement(s)

None required.

Other hazards

Other hazards which do not result in classification:

Burning produces obnoxious and toxic fumes. May be mildly irritating to eyes and skin. May cause respiratory tract irritation. Ingestion can cause gastrointestinal irritation, nausea, and diarrhea. May have laxative effects. Oils can block the skin pores causing an acne-like disorder. Overexposure to sprays or mists may cause chemical pneumonitis (inflammation of lung tissue).

Environmental precautions:

Avoid release to the environment. See ECOLOGICAL INFORMATION, Section 12.



Dual Purpose Vacuum Pump Oil

L339; L340; L341

SDS Revision Date (mm/dd/yyyy): 02/08/2019

Page 2 of 10

SAFETY DATA SHEET

SECTION 3. COMPOSITION/INFORMATION ON INGREDIENTS

<u>Chemical name</u>	<u>Common name and synonyms</u>	<u>CAS #</u>	<u>Concentration (% by weight)</u>
Solvent refined heavy paraffinic distillate	Heavy paraffinic oil	64741-88-4	80.0 - 100.0

The exact concentrations of the above listed chemicals are being withheld as a trade secret.

SECTION 4. FIRST-AID MEASURES

Description of first aid measures

- Ingestion* : Do NOT induce vomiting. Never give anything by mouth to an unconscious person. Get medical attention if symptoms persist.
- Inhalation* : Move to fresh air. If breathing is difficult, give oxygen by qualified medical personnel only. If breathing has stopped, give artificial respiration. If irritation or symptoms develop, seek medical attention.
- Skin contact* : For skin contact, wash with soap and water while removing contaminated clothing. If irritation persists, seek prompt medical attention. Wash contaminated clothing before reuse.
- Eye contact* : Immediately flush eyes with running water for at least 5 to 10 minutes. If irritation persists, seek prompt medical attention.

Most important symptoms and effects, both acute and delayed

- : May be mildly irritating to eyes and skin. May cause respiratory irritation. Ingestion may cause gastrointestinal irritation, nausea, vomiting and diarrhea. May have laxative effects. Oils can block the skin pores causing an acne-like disorder. Overexposure to sprays or mists may cause chemical pneumonitis (inflammation of lung tissue).

Indication of any immediate medical attention and special treatment needed

- : Treat symptomatically.

SECTION 5. FIRE-FIGHTING MEASURES

Extinguishing media

Suitable extinguishing media

- : Use media suitable to the surrounding fire such as water fog or fine spray, alcohol foams, carbon dioxide and dry chemical.

Unsuitable extinguishing media

- : Do not use water jet, as this may spread burning material.

Special hazards arising from the substance or mixture / Conditions of flammability

- : Not flammable under normal conditions of use. However, may ignite if exposed to extreme heat and flame. Closed containers may rupture if exposed to excess heat or flame due to a build-up of internal pressure.

Flammability classification (OSHA 29 CFR 1910.106)

- : Non-flammable.

Hazardous combustion products

- : Nitrogen oxides Phosphorus compounds Hydrocarbons Carbon oxides

Special protective equipment and precautions for firefighters

Protective equipment for fire-fighters

- : Firefighters should wear proper protective equipment and self-contained breathing apparatus with full face piece operated in positive pressure mode.

Special fire-fighting procedures

- : Move containers from fire area if safe to do so. Water spray may be useful in cooling equipment exposed to heat and flame.



Dual Purpose Vacuum Pump Oil

L339; L340; L341

SDS Revision Date (mm/dd/yyyy): 02/08/2019

Page 3 of 10

SAFETY DATA SHEET

SECTION 6. ACCIDENTAL RELEASE MEASURES

Personal precautions, protective equipment and emergency procedures

- : Restrict access to area until completion of clean-up. Ensure clean-up is conducted by trained personnel only. All persons dealing with the clean-up should wear the appropriate chemically protective equipment. Material can create slippery conditions. Refer to protective measures listed in sections 7 and 8.

Environmental precautions : Ensure spilled product does not enter drains, sewers, waterways, or confined spaces.

Methods and material for containment and cleaning up

- : Remove all sources of ignition. Ventilate area of release. Stop the spill at source if it is safe to do so. Dike for water control. Contain and absorb spilled liquid with non-combustible, inert absorbent material (e.g. sand), then place absorbent material into a container for later disposal (see Section 13). Notify the appropriate authorities as required.

Special spill response procedures

- : If a spill/release in excess of the EPA reportable quantity is made into the environment, immediately notify the national response center in the United States (phone: 1-800-424-8802).
US CERCLA Reportable quantity (RQ): None.

SECTION 7. HANDLING AND STORAGE

Precautions for safe handling

- : Wear protective equipment during handling. Use with adequate ventilation. Avoid breathing fumes or vapors. Avoid contact with skin, eyes and clothing. Keep away from extreme heat and flame. Keep away from acids and incompatibles. Keep containers closed when not in use. Wash thoroughly after handling.

Conditions for safe storage : Keep containers tightly closed in a cool, well-ventilated place. Keep away from heat. Inspect periodically for damage or leaks. Protect against physical damage. Storage area should be clearly identified, clear of obstruction and accessible only to trained and authorized personnel.

Incompatible materials : Oxidizing agents.

SECTION 8. EXPOSURE CONTROLS / PERSONAL PROTECTION

<u>Exposure Limits:</u>			
<u>Chemical Name</u>	<u>ACGIH TLV</u>		<u>OSHA PEL</u>
	<u>TWA</u>	<u>STEL</u>	<u>PEL</u> <u>STEL</u>
Solvent refined heavy paraffinic distillate	5 mg/m ³ (inhalable) (As 'Oil mist, mineral')	N/Av	5 mg/m ³ (As 'Oil mist, mineral') N/Av

Exposure controls

Ventilation and engineering measures

- : Use with adequate ventilation. Use general or local exhaust ventilation to maintain air concentrations below recommended exposure limits.

Respiratory protection : If the TLV is exceeded, a NIOSH/MSHA-approved respirator is advised. Advice should be sought from respiratory protection specialists.

Skin protection : Gloves impervious to the material are recommended. Advice should be sought from glove suppliers.

Eye / face protection : Safety goggles or glasses as appropriate for the job.



Dual Purpose Vacuum Pump Oil

L339; L340; L341

SDS Revision Date (mm/dd/yyyy): 02/08/2019

Page 4 of 10

SAFETY DATA SHEET

Other protective equipment : Where extensive exposure to product is possible, use resistant coveralls, apron and boots to prevent contact. Ensure that eyewash stations and safety showers are close to the workstation location.

General hygiene considerations

: Avoid breathing vapors, fumes or dust. Avoid contact with skin, eyes and clothing. Do not eat, drink or smoke when using this product. Wash thoroughly after handling. Remove and wash contaminated clothing before re-use.

SECTION 9. PHYSICAL AND CHEMICAL PROPERTIES

Appearance : Amber liquid.
Odour : Petroleum odor.
Odour threshold : N/Av
pH : N/Av
Melting/Freezing point : Pour point -23°C(-10°F)

Initial boiling point and boiling range

: N/Av

Flash point : 240°C (465°F)

Flashpoint (Method) : open cup

Evaporation rate (BuAe = 1) : N/Av

Flammability (solid, gas) : Not flammable.

Lower flammable limit (% by vol.)

: N/Av

Upper flammable limit (% by vol.)

: N/Av

Oxidizing properties : None known.

Explosive properties : Not explosive

Vapour pressure : <0.0001

Vapour density : N/Av

Relative density / Specific gravity

: 0.87

Solubility in water : insoluble

Other solubility(ies) : N/Av

Partition coefficient: n-octanol/water or Coefficient of water/oil distribution

: N/Av

Auto-ignition temperature : N/Av

Decomposition temperature : N/Av

Viscosity : N/Av

Volatiles (% by weight) : N/Av

Volatile organic Compounds (VOC's)

: N/Av

Absolute pressure of container

: N/Av

Flame projection length : N/Av

Other physical/chemical comments

: No additional information.

SECTION 10. STABILITY AND REACTIVITY

Reactivity : Not normally reactive.

Chemical stability : Stable under the recommended storage and handling conditions prescribed.



Dual Purpose Vacuum Pump Oil

L339; L340; L341

SDS Revision Date (mm/dd/yyyy): 02/08/2019

Page 5 of 10

SAFETY DATA SHEET

Possibility of hazardous reactions

: Hazardous polymerization will not occur.

Conditions to avoid

: Avoid heat and open flame. Avoid contact with incompatible materials. Do not use in areas without adequate ventilation.

Incompatible materials

: Acids; Oxidizing agents.

Hazardous decomposition products

: None known, refer to hazardous combustion products in Section 5.

SECTION 11. TOXICOLOGICAL INFORMATION

Information on likely routes of exposure:

Routes of entry inhalation : YES

Routes of entry skin & eye : YES

Routes of entry Ingestion : YES

Routes of exposure skin absorption

: NO

Potential Health Effects:

Signs and symptoms of short-term (acute) exposure

Sign and symptoms Inhalation

: May cause respiratory tract irritation. Overexposure to sprays or mists may cause chemical pneumonitis (inflammation of lung tissue).

Sign and symptoms ingestion

: Ingestion may cause gastrointestinal irritation, nausea, vomiting and diarrhea. May have laxative effects.

Sign and symptoms skin

: Direct skin contact may cause slight or mild, transient irritation.

Sign and symptoms eyes

: May cause mild irritation, redness and watering.

Potential Chronic Health Effects

: Oils can block the skin pores causing an acne-like disorder. Overexposure to sprays or mists may cause chemical pneumonitis (inflammation of lung tissue).

Mutagenicity

: Not expected to be mutagenic.

Carcinogenicity

: This product does not meet the criteria for carcinogens under OSHA regulations (29 CFR 1910.1200) (Hazcom 2012). No components are listed as carcinogens by ACGIH, IARC, OSHA or NTP. The following petroleum derived chemicals contain < 3% DMSO: Solvent refined heavy paraffinic distillate

Reproductive effects & Teratogenicity

: Not expected to cause reproductive effects.

Sensitization to material

: Not expected to be a skin or respiratory sensitizer.

Specific target organ effects

: Not classified as a specific target organ toxicity-single exposure. Not classified as specific target organ toxicity-repeated exposure.

Medical conditions aggravated by overexposure

: Pre-existing skin and respiratory disorders.

Synergistic materials

: Not available.

Toxicological data

: See below for individual ingredient acute toxicity data. Contains no ingredients that are considered to have acute toxicity hazards.



Dual Purpose Vacuum Pump Oil

L339; L340; L341

SDS Revision Date (mm/dd/yyyy): 02/08/2019

Page 6 of 10

SAFETY DATA SHEET

<u>Chemical name</u>	<u>LC₅₀(4hr)</u>	<u>LD₅₀</u>	
	<u>inh, rat</u>	<u>(Oral, rat)</u>	<u>(Rabbit, dermal)</u>
Solvent refined heavy paraffinic distillate	5.53mg/L	> 5000 mg/kg	> 2000 mg/kg

Other important toxicological hazards

: None known or reported by the manufacturer.

SECTION 12. ECOLOGICAL INFORMATION

Ecotoxicity : The product should not be allowed to enter drains or water courses, or be deposited where it can affect ground or surface waters. See the following tables for individual ingredient ecotoxicity data.

Ecotoxicity data:

<u>Ingredients</u>	<u>CAS No</u>	<u>Toxicity to Fish</u>		
		<u>LC50 / 96h</u>	<u>NOEC / 21 day</u>	<u>M Factor</u>
Solvent refined heavy paraffinic distillate	64741-88-4	> 100 mg/L (Fathead minnow)	N/Av	None.

<u>Ingredients</u>	<u>CAS No</u>	<u>Toxicity to Daphnia</u>		
		<u>EC50 / 48h</u>	<u>NOEC / 21 day</u>	<u>M Factor</u>
Solvent refined heavy paraffinic distillate	64741-88-4	> 10000mg/L (Daphnia magna)	N/Av	None.

<u>Ingredients</u>	<u>CAS No</u>	<u>Toxicity to Algae</u>		
		<u>EC50 / 96h or 72h</u>	<u>NOEC / 96h or 72h</u>	<u>M Factor</u>
Solvent refined heavy paraffinic distillate	64741-88-4	>100mg/L (Green algae)	N/Av	None.

Persistence and degradability

: Inherently biodegradable.

Bioaccumulation potential

: The product itself has not been tested.

<u>Components</u>	<u>Partition coefficient n-octanol/water (log Kow)</u>	<u>Bioconcentration factor (BCF)</u>
Solvent refined heavy paraffinic distillate (CAS 64741-88-4)	>5.7	N/Av

Mobility in soil : The product itself has not been tested.

Other Adverse Environmental effects

: None known.

SECTION 13. DISPOSAL CONSIDERATIONS

Handling for Disposal

: Handle waste according to recommendations in Section 7.

Methods of Disposal

: Dispose in accordance with all applicable federal, state, provincial and local regulations.



Dual Purpose Vacuum Pump Oil

L339; L340; L341

SDS Revision Date (mm/dd/yyyy): 02/08/2019

Page 7 of 10

SAFETY DATA SHEET

RCRA

: If this product, as supplied, becomes a waste in the United States, it may meet the criteria of a hazardous waste as defined under RCRA, Title 40 CFR 261. It is the responsibility of the waste generator to determine the proper waste identification and disposal method. For disposal of unused or waste material, check with local, state and federal environmental agencies.

SECTION 14. TRANSPORT INFORMATION

Regulatory Information	UN Number	UN proper shipping name	Transport hazard class(es)	Packing Group	Label
49CFR/DOT	None.	Not regulated.	Not regulated	none	
49CFR/DOT Additional information	None.				
TDG	None.	Not regulated.	Not regulated	none	
TDG Additional information	None.				
ICAO/IATA	None.	Not regulated.	Not regulated	none	
ICAO/IATA Additional information	None.				

Special precautions for user : Appropriate advice on safety must accompany the package.

Environmental hazards : This substance does not meet the criteria for an environmentally hazardous substance according to the IMDG Code. See ECOLOGICAL INFORMATION, Section 12.

Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code

: This information is not available.

SECTION 15 - REGULATORY INFORMATION

US Federal Information:

Components listed below are present on the following U.S. Federal chemical lists:

Ingredients	CAS #	TSCA Inventory	CERCLA Reportable Quantity(RQ) (40 CFR 117.302):	SARA TITLE III: Sec. 302, Extremely Hazardous Substance, 40 CFR 355:	SARA TITLE III: Sec. 313, 40 CFR 372, Specific Toxic Chemical	de minimus Concentration
Solvent refined heavy paraffinic distillate	64741-88-4	Yes	N/Ap	N/Av	Toxic Chemical No	N/Ap

SARA TITLE III: Sec. 311 and 312, SDS Requirements, 40 CFR 370 Hazard Classes: None.

Under SARA Sections 311 and 312, the EPA has established threshold quantities for the reporting of hazardous chemicals. The current thresholds are 500 pounds or the threshold planning quantity (TPQ), whichever is lower, for extremely hazardous substances and 10,000 pounds for all other hazardous chemicals.



Parker Hannifin Corporation - Sporlan Division
206 Lange Drive
Washington, MO, U.S.A., 63090
Telephone: (636) 239 1111

Dual Purpose Vacuum Pump Oil

L339; L340; L341

SDS Revision Date (mm/dd/yyyy): 02/08/2019

Page 8 of 10

SAFETY DATA SHEET

US State Right to Know Laws:

The following chemicals are specifically listed by individual States:

<u>Ingredients</u>	CAS #	California Proposition 65		State "Right to Know" Lists					
		Listed	Type of Toxicity	CA	MA	MN	NJ	PA	RI
Solvent refined heavy paraffinic distillate	64741-88-4	No	N/Ap	No	No	No	No	No	No

Canadian Information:

Canadian Environmental Protection Act (CEPA) information: All ingredients listed appear on the Domestic Substances List (DSL).

WHMIS information: Refer to Section 2 for a WHMIS Classification for this product.

International Information:

Components listed below are present on the following International Inventory list:

<u>Ingredients</u>	CAS #	European EINECS	Australia AICS	Philippines PICCS	Japan ENCS	Korea KECI/KECL	China IECSC	New Zealand IOC
Solvent refined heavy paraffinic distillate	64741-88-4	265-090-8	Present	Present	(9)-1692	KE-12614	Present	May be used as a single component chemical under an appropriate group standard.

SECTION 16. OTHER INFORMATION

Legend

: ACGIH: American Conference of Governmental Industrial Hygienists
CA: California
CAS: Chemical Abstract Services
CERCLA: Comprehensive Environmental Response, Compensation, and Liability Act of 1980
CFR: Code of Federal Regulations
DOT: Department of Transportation
EPA: Environmental Protection Agency
HMIS: Hazardous Materials Identification System
HSDB: Hazardous Substances Data Bank
IARC: International Agency for Research on Cancer
Inh: Inhalation
IUCLID: International Uniform Chemical Information Database
MA: Massachusetts
MN: Minnesota
mppcf: million particles per cubic foot
MSHA: Mine Safety and Health Administration
N/Ap: Not Applicable
N/Av: Not Available
NFPA: National Fire Protection Association
NIOSH: National Institute of Occupational Safety and Health
NJ: New Jersey
NTP: National Toxicology Program



Parker Hannifin Corporation - Sporlan Division
206 Lange Drive
Washington, MO, U.S.A., 63090
Telephone: (636) 239 1111

Dual Purpose Vacuum Pump Oil

L339; L340; L341

SDS Revision Date (mm/dd/yyyy): 02/08/2019

Page 9 of 10

SAFETY DATA SHEET

OSHA: Occupational Safety and Health Administration
PA: Pennsylvania
PEL: Permissible exposure limit
RCRA: Resource Conservation and Recovery Act
RI: Rhode Island
RTECS: Registry of Toxic Effects of Chemical Substances
SARA: Superfund Amendments and Reauthorization Act
STEL: Short Term Exposure Limit
TDG: Canadian Transportation of Dangerous Goods Act & Regulations
TLV: Threshold Limit Values
TWA: Time Weighted Average
WHMIS: Workplace Hazardous Materials Identification System

References

- : 1. ACGIH, Threshold Limit Values for Chemical Substances and Physical Agents & Biological Exposure Indices for 2016
- 2. International Agency for Research on Cancer Monographs, searched 2017
- 3. Canadian Centre for Occupational Health and Safety, CCInfoWeb databases, 2017(Chempendium, HSDB and RTECs).
- 4. Material Safety Data Sheets from manufacturer.
- 5. US EPA Title III List of Lists - 2017 version.
- 6. California Proposition 65 List - 2017 version.
- 7. OECD - The Global Portal to Information on Chemical Substances - eChemPortal, 2017.

Preparation Date (mm/dd/yyyy)

: 08/06/2015

Reviewed Date SDS (dd/mm/yyyy)

: 08/02/2019

Revision No.

: 4

Revision Information

: All (format change)

Other special considerations for handling

: Provide adequate information, instruction and training for operators.

HMIS Rating

: *- Chronic hazard 0 - Minimal 1 - Slight 2 - Moderate 3 - Serious 4 - Severe
Health: 1 Flammability: 1 Reactivity: 0

NFPA Rating

0 - Minimal 1 - Slight 2 - Moderate 3 - Serious 4 - Severe
: Health: 1 Flammability: 1 Instability: 0 Special Hazards: None.

Prepared for:

Parker Hannifin Corporation Sporlan Division
206 Lange Drive, Washington, MO 63090 U.S.A.
Telephone: (636) 239-1111
www.parker.com
Direct all enquiries to: Parker Hannifin Corp. Sporlan Division.



Prepared by:

ICC The Compliance Center Inc.
Telephone: (888) 442-9628 (U.S.): (888) 977-4834 (Canada)
<http://www.thecompliancecenter.com>



DISCLAIMER

This Safety Data Sheet was prepared by ICC The Compliance Center Inc. using information provided by Parker Hannifin Corporation and CCOHS' Web Information Service. The information in the Safety Data Sheet is offered for your consideration and guidance when exposed to this product. ICC The Compliance Center Inc and Parker Hannifin Corporation expressly disclaim all expressed or implied warranties and assume no responsibilities for the accuracy or completeness of the data contained herein. The data in this SDS does not apply to use with any other product or in any

Dual Purpose Vacuum Pump Oil

L339; L340; L341

SDS Revision Date (mm/dd/yyyy): 02/08/2019

Page 10 of 10

SAFETY DATA SHEET

other process.

This Safety Data Sheet may not be changed, or altered in any way without the expressed knowledge and permission of ICC The Compliance Center Inc. and Parker Hannifin Corporation.

END OF DOCUMENT