



FY2024 SDS Binder

Section 36

Krylon LU™620 Anti-Seize Compound, Aerosol

Page Intentionally Left Blank

SAFETY DATA SHEET

SC0620000

Section 1. Identification

Product name : LU™620 Anti-Seize Compound Aerosol
Product code : SC0620000
Other means of identification : Not available.
Product type : Aerosol.
Relevant identified uses of the substance or mixture and uses advised against

Paint or paint related material.

Manufacturer : Sprayon Products Group
 101 W. Prospect Avenue,
 Cleveland, Ohio 44115

Emergency telephone number of the company : US / Canada: (800) 424-9300
 Mexico: SETIQ 800-00-214-00 / 55-5559-1588 Available 24 hours and 365 days a year

Product Information Telephone Number : US / Canada: (800) 247-3266
 Mexico: Not Available

Regulatory Information Telephone Number : US / Canada: (216) 566-2902
 Mexico: Not Available

Transportation Emergency Telephone Number : US / Canada: (800) 424-9300
 Mexico: SETIQ 800-00-214-00 / 55-5559-1588 Available 24 hours and 365 days a year


Section 2. Hazards identification

OSHA/HCS status : This material is considered hazardous by the OSHA Hazard Communication Standard (29 CFR 1910.1200).

Classification of the substance or mixture : FLAMMABLE AEROSOLS - Category 1
 GASES UNDER PRESSURE - Compressed gas
 SKIN CORROSION/IRRITATION - Category 2
 SPECIFIC TARGET ORGAN TOXICITY (SINGLE EXPOSURE) (Respiratory tract irritation) - Category 3
 SPECIFIC TARGET ORGAN TOXICITY (SINGLE EXPOSURE) (Narcotic effects) - Category 3
 SPECIFIC TARGET ORGAN TOXICITY (REPEATED EXPOSURE) - Category 2
 ASPIRATION HAZARD - Category 1
 Percentage of the mixture consisting of ingredient(s) of unknown acute toxicity: 17.5% (oral), 19.1% (dermal), 52.4% (inhalation)

GHS label elements

Hazard pictograms



Signal word

: Danger

Date of issue/Date of revision : 9/22/2021 **Date of previous issue** : 4/19/2021

SC0620000 LU™620 Anti-Seize Compound Aerosol

Version : 13.01 1/16

SHW-85-NA-GHS-US

Section 2. Hazards identification

- Hazard statements** : Extremely flammable aerosol.
 Contains gas under pressure; may explode if heated.
 May be fatal if swallowed and enters airways.
 Causes skin irritation.
 May cause respiratory irritation.
 May cause drowsiness or dizziness.
 May cause damage to organs through prolonged or repeated exposure.
- Precautionary statements**
- Prevention** : Wear protective gloves. Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking. Do not spray on an open flame or other ignition source. Use only outdoors or in a well-ventilated area. Do not breathe dust or mist. Wash thoroughly after handling. Pressurized container: Do not pierce or burn, even after use.
- Response** : IF INHALED: Remove person to fresh air and keep comfortable for breathing. Call a POISON CENTER or doctor if you feel unwell. IF SWALLOWED: Immediately call a POISON CENTER or doctor. Do NOT induce vomiting. Take off contaminated clothing and wash it before reuse. IF ON SKIN: Wash with plenty of water. If skin irritation occurs: Get medical advice or attention.
- Storage** : Store locked up. Protect from sunlight. Do not expose to temperatures exceeding 50 °C/122 °F. Store in a well-ventilated place. Keep container tightly closed.
- Disposal** : Dispose of contents and container in accordance with all local, regional, national and international regulations.
- Supplemental label elements** DELAYED EFFECTS FROM LONG TERM OVEREXPOSURE. Contains solvents which can cause permanent brain and nervous system damage. Intentional misuse by deliberately concentrating and inhaling the contents can be harmful or fatal. WARNING: This product contains a chemical known to the State of California to cause birth defects or other reproductive harm. FOR INDUSTRIAL USE ONLY.
 Please refer to the SDS for additional information. Keep out of reach of children. Keep upright in a cool, dry place. Do not discard empty can in trash compactor.
- Hazards not otherwise classified** : None known.

Section 3. Composition/information on ingredients

- Substance/mixture** : Mixture
- Other means of identification** : Not available.
- CAS number/other identifiers**

Ingredient name	% by weight	CAS number
Light Aliphatic Hydrocarbon Solvent	≥25 - ≤50	64742-49-0
Propane	≥10 - ≤25	74-98-6
Heavy Paraffinic Oil	≥10 - ≤25	64742-54-7
Butane	≥10 - ≤25	106-97-8
Graphite	≤10	7782-42-5
Lt. Aliphatic Hydrocarbon Solvent	≤3	64742-89-8
Methyl Cyclohexane	≤3	108-87-2
Copper	≤3	7440-50-8
Fumed Amorphous Silica	≤3	112945-52-5

Any concentration shown as a range is to protect confidentiality or is due to batch variation.

There are no additional ingredients present which, within the current knowledge of the supplier and in the concentrations applicable, are classified and hence require reporting in this section.

Occupational exposure limits, if available, are listed in Section 8.

Section 4. First aid measures

Description of necessary first aid measures

- Eye contact** : Immediately flush eyes with plenty of water, occasionally lifting the upper and lower eyelids. Check for and remove any contact lenses. Continue to rinse for at least 10 minutes. Get medical attention.
- Inhalation** : Remove victim to fresh air and keep at rest in a position comfortable for breathing. If it is suspected that fumes are still present, the rescuer should wear an appropriate mask or self-contained breathing apparatus. If not breathing, if breathing is irregular or if respiratory arrest occurs, provide artificial respiration or oxygen by trained personnel. It may be dangerous to the person providing aid to give mouth-to-mouth resuscitation. Get medical attention. If necessary, call a poison center or physician. If unconscious, place in recovery position and get medical attention immediately. Maintain an open airway. Loosen tight clothing such as a collar, tie, belt or waistband.
- Skin contact** : Flush contaminated skin with plenty of water. Remove contaminated clothing and shoes. Continue to rinse for at least 10 minutes. Get medical attention. Wash clothing before reuse. Clean shoes thoroughly before reuse.
- Ingestion** : Get medical attention immediately. Call a poison center or physician. Wash out mouth with water. Remove dentures if any. If material has been swallowed and the exposed person is conscious, give small quantities of water to drink. Stop if the exposed person feels sick as vomiting may be dangerous. Aspiration hazard if swallowed. Can enter lungs and cause damage. Do not induce vomiting. If vomiting occurs, the head should be kept low so that vomit does not enter the lungs. Never give anything by mouth to an unconscious person. If unconscious, place in recovery position and get medical attention immediately. Maintain an open airway. Loosen tight clothing such as a collar, tie, belt or waistband.

Most important symptoms/effects, acute and delayed

Potential acute health effects

- Eye contact** : No known significant effects or critical hazards.
- Inhalation** : Can cause central nervous system (CNS) depression. May cause drowsiness or dizziness. May cause respiratory irritation.
- Skin contact** : Causes skin irritation.
- Ingestion** : Can cause central nervous system (CNS) depression. May be fatal if swallowed and enters airways.

Over-exposure signs/symptoms

- Eye contact** : Adverse symptoms may include the following:
pain or irritation
watering
redness
- Inhalation** : Adverse symptoms may include the following:
respiratory tract irritation
coughing
nausea or vomiting
headache
drowsiness/fatigue
dizziness/vertigo
unconsciousness
- Skin contact** : Adverse symptoms may include the following:
irritation
redness
- Ingestion** : Adverse symptoms may include the following:
nausea or vomiting

Indication of immediate medical attention and special treatment needed, if necessary

Section 4. First aid measures

- Notes to physician** : Treat symptomatically. Contact poison treatment specialist immediately if large quantities have been ingested or inhaled.
- Specific treatments** : No specific treatment.
- Protection of first-aiders** : No action shall be taken involving any personal risk or without suitable training. If it is suspected that fumes are still present, the rescuer should wear an appropriate mask or self-contained breathing apparatus. It may be dangerous to the person providing aid to give mouth-to-mouth resuscitation.

See toxicological information (Section 11)

Section 5. Fire-fighting measures

Extinguishing media

- Suitable extinguishing media** : Use an extinguishing agent suitable for the surrounding fire.
- Unsuitable extinguishing media** : None known.

- Specific hazards arising from the chemical** : Extremely flammable aerosol. Runoff to sewer may create fire or explosion hazard. In a fire or if heated, a pressure increase will occur and the container may burst, with the risk of a subsequent explosion. Gas may accumulate in low or confined areas or travel a considerable distance to a source of ignition and flash back, causing fire or explosion. Bursting aerosol containers may be propelled from a fire at high speed.

- Hazardous thermal decomposition products** : Decomposition products may include the following materials:
carbon dioxide
carbon monoxide
metal oxide/oxides

- Special protective actions for fire-fighters** : Promptly isolate the scene by removing all persons from the vicinity of the incident if there is a fire. No action shall be taken involving any personal risk or without suitable training. Move containers from fire area if this can be done without risk. Use water spray to keep fire-exposed containers cool.

- Special protective equipment for fire-fighters** : Fire-fighters should wear appropriate protective equipment and self-contained breathing apparatus (SCBA) with a full face-piece operated in positive pressure mode.

Section 6. Accidental release measures

Personal precautions, protective equipment and emergency procedures

- For non-emergency personnel** : No action shall be taken involving any personal risk or without suitable training. Evacuate surrounding areas. Keep unnecessary and unprotected personnel from entering. In the case of aerosols being ruptured, care should be taken due to the rapid escape of the pressurized contents and propellant. If a large number of containers are ruptured, treat as a bulk material spillage according to the instructions in the clean-up section. Do not touch or walk through spilled material. Shut off all ignition sources. No flares, smoking or flames in hazard area. Avoid breathing vapor or mist. Provide adequate ventilation. Wear appropriate respirator when ventilation is inadequate. Put on appropriate personal protective equipment.

- For emergency responders** : If specialized clothing is required to deal with the spillage, take note of any information in Section 8 on suitable and unsuitable materials. See also the information in "For non-emergency personnel".

- Environmental precautions** : Avoid dispersal of spilled material and runoff and contact with soil, waterways, drains and sewers. Inform the relevant authorities if the product has caused environmental pollution (sewers, waterways, soil or air).

Section 6. Accidental release measures

Methods and materials for containment and cleaning up

- Small spill** : Stop leak if without risk. Move containers from spill area. Use spark-proof tools and explosion-proof equipment. Dilute with water and mop up if water-soluble. Alternatively, or if water-insoluble, absorb with an inert dry material and place in an appropriate waste disposal container. Dispose of via a licensed waste disposal contractor.
- Large spill** : Stop leak if without risk. Move containers from spill area. Use spark-proof tools and explosion-proof equipment. Approach release from upwind. Prevent entry into sewers, water courses, basements or confined areas. Wash spillages into an effluent treatment plant or proceed as follows. Contain and collect spillage with non-combustible, absorbent material e.g. sand, earth, vermiculite or diatomaceous earth and place in container for disposal according to local regulations (see Section 13). Dispose of via a licensed waste disposal contractor. Contaminated absorbent material may pose the same hazard as the spilled product. Note: see Section 1 for emergency contact information and Section 13 for waste disposal.

Section 7. Handling and storage

Precautions for safe handling

- Protective measures** : Put on appropriate personal protective equipment (see Section 8). Pressurized container: protect from sunlight and do not expose to temperatures exceeding 50°C. Do not pierce or burn, even after use. Do not breathe vapor or mist. Do not swallow. Avoid contact with eyes, skin and clothing. Avoid breathing gas. Use only with adequate ventilation. Wear appropriate respirator when ventilation is inadequate. Store and use away from heat, sparks, open flame or any other ignition source. Use explosion-proof electrical (ventilating, lighting and material handling) equipment. Use only non-sparking tools. Empty containers retain product residue and can be hazardous.

- Advice on general occupational hygiene** : Eating, drinking and smoking should be prohibited in areas where this material is handled, stored and processed. Workers should wash hands and face before eating, drinking and smoking. Remove contaminated clothing and protective equipment before entering eating areas. See also Section 8 for additional information on hygiene measures.

- Conditions for safe storage, including any incompatibilities** : Store in accordance with local regulations. Store away from direct sunlight in a dry, cool and well-ventilated area, away from incompatible materials (see Section 10) and food and drink. Protect from sunlight. Store locked up. Eliminate all ignition sources. Use appropriate containment to avoid environmental contamination. See Section 10 for incompatible materials before handling or use.

Section 8. Exposure controls/personal protection

Control parameters

Occupational exposure limits (OSHA United States)

Ingredient name	CAS #	Exposure limits
Light Aliphatic Hydrocarbon Solvent Propane	64742-49-0 74-98-6	None. NIOSH REL (United States, 10/2020). TWA: 1000 ppm 10 hours. TWA: 1800 mg/m ³ 10 hours. OSHA PEL (United States, 5/2018). TWA: 1000 ppm 8 hours. TWA: 1800 mg/m ³ 8 hours.
Heavy Paraffinic Oil	64742-54-7	ACGIH TLV (United States, 1/2021). Oxygen Depletion [Asphyxiant]. Explosive potential. OSHA PEL (United States, 5/2018). TWA: 5 mg/m ³ 8 hours. ACGIH TLV (United States, 1/2021). TWA: 5 mg/m ³ 8 hours. Form: Inhalable

Section 8. Exposure controls/personal protection

Butane	106-97-8	fraction NIOSH REL (United States, 10/2020). TWA: 5 mg/m ³ 10 hours. Form: Mist STEL: 10 mg/m ³ 15 minutes. Form: Mist NIOSH REL (United States, 10/2020). TWA: 800 ppm 10 hours. TWA: 1900 mg/m ³ 10 hours. ACGIH TLV (United States, 1/2021). Explosive potential. STEL: 1000 ppm 15 minutes.
Graphite	7782-42-5	ACGIH TLV (United States, 1/2021). TWA: 2 mg/m ³ 8 hours. Form: Respirable fraction NIOSH REL (United States, 10/2020). TWA: 2.5 mg/m ³ 10 hours. Form: Respirable fraction OSHA PEL (United States, 5/2018). TWA: 5 mg/m ³ 8 hours. Form: Respirable fraction TWA: 15 mg/m ³ 8 hours. Form: Total dust OSHA PEL Z3 (United States, 6/2016). TWA: 15 mppcf 8 hours.
Lt. Aliphatic Hydrocarbon Solvent Methyl Cyclohexane	64742-89-8 108-87-2	None. ACGIH TLV (United States, 1/2021). TWA: 400 ppm 8 hours. TWA: 1610 mg/m ³ 8 hours. NIOSH REL (United States, 10/2020). TWA: 400 ppm 10 hours. TWA: 1600 mg/m ³ 10 hours. OSHA PEL (United States, 5/2018). TWA: 500 ppm 8 hours. TWA: 2000 mg/m ³ 8 hours.
Copper	7440-50-8	ACGIH TLV (United States, 1/2021). TWA: 1 mg/m ³ , (as Cu) 8 hours. Form: Dust and mist TWA: 0.2 mg/m ³ 8 hours. Form: Fume NIOSH REL (United States, 10/2020). TWA: 1 mg/m ³ , (as Cu) 10 hours. Form: Dusts and Mists OSHA PEL (United States, 5/2018). TWA: 1 mg/m ³ 8 hours. Form: Dusts and Mists TWA: 0.1 mg/m ³ 8 hours. Form: Fume
Fumed Amorphous Silica	112945-52-5	NIOSH REL (United States, 10/2020). TWA: 6 mg/m ³ 10 hours.

[Occupational exposure limits \(Canada\)](#)

Ingredient name	CAS #	Exposure limits
Normal propane	74-98-6	CA Alberta Provincial (Canada, 6/2018). 8 hrs OEL: 1000 ppm 8 hours. CA Quebec Provincial (Canada, 7/2019). TWAEV: 1000 ppm 8 hours. TWAEV: 1800 mg/m ³ 8 hours. CA Saskatchewan Provincial (Canada, 7/2013). STEL: 1250 ppm 15 minutes.

Section 8. Exposure controls/personal protection

Heavy Paraffinic Oil	64742-54-7	<p>TWA: 1000 ppm 8 hours. CA British Columbia Provincial (Canada, 1/2021). Oxygen Depletion [Asphyxiant]. Explosive potential.</p>
Butane	106-97-8	<p>CA Ontario Provincial (Canada, 6/2019). Oxygen Depletion [Asphyxiant]. Explosive potential.</p> <p>CA Alberta Provincial (Canada, 6/2018). 8 hrs OEL: 5 mg/m³ 8 hours. Form: Mist 15 min OEL: 10 mg/m³ 15 minutes. Form: Mist</p> <p>CA Quebec Provincial (Canada, 7/2019). TWAEV: 5 mg/m³ 8 hours. Form: mist STEV: 10 mg/m³ 15 minutes. Form: mist</p> <p>CA Alberta Provincial (Canada, 6/2018). 8 hrs OEL: 1000 ppm 8 hours.</p> <p>CA Quebec Provincial (Canada, 7/2019). TWAEV: 800 ppm 8 hours. TWAEV: 1900 mg/m³ 8 hours.</p> <p>CA Saskatchewan Provincial (Canada, 7/2013). STEL: 1250 ppm 15 minutes. TWA: 1000 ppm 8 hours.</p> <p>CA British Columbia Provincial (Canada, 1/2021). Explosive potential. STEL: 1000 ppm 15 minutes.</p> <p>CA Ontario Provincial (Canada, 6/2019). Explosive potential. STEL: 1000 ppm 15 minutes.</p>
Synthetic graphite	7782-42-5	<p>CA British Columbia Provincial (Canada, 1/2021). TWA: 2 mg/m³ 8 hours. Form: Respirable</p> <p>CA Alberta Provincial (Canada, 6/2018). 8 hrs OEL: 2 mg/m³ 8 hours. Form: Respirable (all forms except graphite fibres)</p> <p>CA Quebec Provincial (Canada, 7/2019). TWAEV: 2 mg/m³ 8 hours. Form: Respirable dust.</p> <p>CA Ontario Provincial (Canada, 6/2019). TWA: 2 mg/m³ 8 hours. Form: Respirable particulate matter.</p> <p>CA Saskatchewan Provincial (Canada, 7/2013). STEL: 4 mg/m³ 15 minutes. Form: respirable fraction TWA: 2 mg/m³ 8 hours. Form: respirable fraction</p>
Methylcyclohexane	108-87-2	<p>CA Alberta Provincial (Canada, 6/2018). 8 hrs OEL: 400 ppm 8 hours. 8 hrs OEL: 1610 mg/m³ 8 hours.</p> <p>CA British Columbia Provincial (Canada, 1/2021). TWA: 400 ppm 8 hours.</p> <p>CA Ontario Provincial (Canada, 6/2019). TWA: 400 ppm 8 hours.</p> <p>CA Quebec Provincial (Canada, 7/2019).</p>

Section 8. Exposure controls/personal protection

Copper	7440-50-8	<p>TWAEV: 400 ppm 8 hours. TWAEV: 1610 mg/m³ 8 hours. CA Saskatchewan Provincial (Canada, 7/2013). STEL: 500 ppm 15 minutes. TWA: 400 ppm 8 hours. CA Alberta Provincial (Canada, 6/2018). 8 hrs OEL: 1 mg/m³, (as Cu) 8 hours. Form: Dusts and Mists 8 hrs OEL: 0.2 mg/m³ 8 hours. Form: Fume CA British Columbia Provincial (Canada, 1/2021). TWA: 1 mg/m³, (as Cu) 8 hours. Form: Dusts and mists TWA: 0.2 mg/m³, (as Cu) 8 hours. Form: Fume CA Ontario Provincial (Canada, 6/2019). TWA: 0.2 mg/m³, (as Cu) 8 hours. Form: Fume TWA: 1 mg/m³, (as Cu) 8 hours. Form: dust and mists CA Saskatchewan Provincial (Canada, 7/2013). STEL: 0.6 mg/m³, (measured as Cu) 15 minutes. Form: Fume TWA: 0.2 mg/m³, (measured as Cu) 8 hours. Form: Fume STEL: 3 mg/m³, (measured as Cu) 15 minutes. Form: dust and mist TWA: 1 mg/m³, (measured as Cu) 8 hours. Form: dust and mist CA Quebec Provincial (Canada, 7/2019). TWAEV: 1 mg/m³, (as Cu) 8 hours. Form: dusts & mists TWAEV: 0.2 mg/m³, (as Cu) 8 hours. Form: fume</p>
--------	-----------	-------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------

[Occupational exposure limits \(Mexico\)](#)

	CAS #	Exposure limits
Propane	74-98-6	NOM-010-STPS-2014 (Mexico, 4/2016). TWA: 1000 ppm 8 hours.
Heavy Paraffinic Oil	64742-54-7	NOM-010-STPS-2014 (Mexico, 4/2016). TWA: 5 mg/m ³ 8 hours. Form: mist
Butane	106-97-8	NOM-010-STPS-2014 (Mexico, 4/2016). TWA: 1000 ppm 8 hours.
Methyl Cyclohexane	108-87-2	NOM-010-STPS-2014 (Mexico, 4/2016). TWA: 400 ppm 8 hours.
Copper	7440-50-8	NOM-010-STPS-2014 (Mexico, 4/2016). TWA: 0.2 mg/m ³ , (as Cu) 8 hours. Form: Fumes TWA: 1 mg/m ³ , (as Cu) 8 hours. Form: powder and mist

Section 8. Exposure controls/personal protection

- Appropriate engineering controls** : Use only with adequate ventilation. Use process enclosures, local exhaust ventilation or other engineering controls to keep worker exposure to airborne contaminants below any recommended or statutory limits. The engineering controls also need to keep gas, vapor or dust concentrations below any lower explosive limits. Use explosion-proof ventilation equipment.
- Environmental exposure controls** : Emissions from ventilation or work process equipment should be checked to ensure they comply with the requirements of environmental protection legislation. In some cases, fume scrubbers, filters or engineering modifications to the process equipment will be necessary to reduce emissions to acceptable levels.
- Individual protection measures**
- Hygiene measures** : Wash hands, forearms and face thoroughly after handling chemical products, before eating, smoking and using the lavatory and at the end of the working period. Appropriate techniques should be used to remove potentially contaminated clothing. Wash contaminated clothing before reusing. Ensure that eyewash stations and safety showers are close to the workstation location.
- Eye/face protection** : Safety eyewear complying with an approved standard should be used when a risk assessment indicates this is necessary to avoid exposure to liquid splashes, mists, gases or dusts. If contact is possible, the following protection should be worn, unless the assessment indicates a higher degree of protection: chemical splash goggles.
- Skin protection**
- Hand protection** : Chemical-resistant, impervious gloves complying with an approved standard should be worn at all times when handling chemical products if a risk assessment indicates this is necessary. Considering the parameters specified by the glove manufacturer, check during use that the gloves are still retaining their protective properties. It should be noted that the time to breakthrough for any glove material may be different for different glove manufacturers. In the case of mixtures, consisting of several substances, the protection time of the gloves cannot be accurately estimated.
- Body protection** : Personal protective equipment for the body should be selected based on the task being performed and the risks involved and should be approved by a specialist before handling this product. When there is a risk of ignition from static electricity, wear anti-static protective clothing. For the greatest protection from static discharges, clothing should include anti-static overalls, boots and gloves.
- Other skin protection** : Appropriate footwear and any additional skin protection measures should be selected based on the task being performed and the risks involved and should be approved by a specialist before handling this product.
- Respiratory protection** : Based on the hazard and potential for exposure, select a respirator that meets the appropriate standard or certification. Respirators must be used according to a respiratory protection program to ensure proper fitting, training, and other important aspects of use.

Section 9. Physical and chemical properties

The conditions of measurement of all properties are at standard temperature and pressure unless otherwise indicated.

Appearance

- Physical state** : Liquid.
- Color** : Not available.
- Odor** : Not available.
- Odor threshold** : Not available.
- pH** : Not applicable.
- Melting point/freezing point** : Not available.
- Boiling point, initial boiling point, and boiling range** : Not available.
- Flash point** : Closed cup: -29°C (-20.2°F) [Pensky-Martens Closed Cup]

Section 9. Physical and chemical properties

Evaporation rate	: 1.5 (butyl acetate = 1)	
Flammability	: Not available.	
Lower and upper explosion limit/flammability limit	: Lower: 0.9% Upper: 9.5%	
Vapor pressure	: 101.3 kPa (760 mm Hg)	▼
Relative vapor density	: 1.55 [Air = 1]	
Relative density	: 0.72	
Solubility	: Not available.	
Partition coefficient: n-octanol/water	: Not applicable.	▼
Auto-ignition temperature	: Not available.	
Decomposition temperature	: Not available.	
Viscosity	: Kinematic (40°C (104°F)): <20.5 mm ² /s (<20.5 cSt)	▼
Molecular weight	: Not applicable.	
Aerosol product		
Type of aerosol	: Spray	
Heat of combustion	: 27.486 kJ/g	

Section 10. Stability and reactivity

Reactivity	: No specific test data related to reactivity available for this product or its ingredients.
Chemical stability	: The product is stable.
Possibility of hazardous reactions	: Under normal conditions of storage and use, hazardous reactions will not occur.
Conditions to avoid	: Avoid all possible sources of ignition (spark or flame).
Incompatible materials	: No specific data.
Hazardous decomposition products	: Under normal conditions of storage and use, hazardous decomposition products should not be produced.

Section 11. Toxicological information

Information on toxicological effects

Acute toxicity

Product/ingredient name	Result	Species	Dose	Exposure
Butane	LC50 Inhalation Vapor	Rat	658000 mg/m ³	4 hours
Fumed Amorphous Silica	LD50 Oral	Rat	3160 mg/kg	-

Irritation/Corrosion

Product/ingredient name	Result	Species	Score	Exposure	Observation
Methyl Cyclohexane	Eyes - Mild irritant	Rabbit	-	24 hours 100 uL	-
	Skin - Mild irritant	Rabbit	-	24 hours 500 uL	-

Sensitization

Date of issue/Date of revision	: 9/22/2021	Date of previous issue	: 4/19/2021	Version	: 13.01	10/16
SC0620000	LU™620 Anti-Seize Compound Aerosol			SHW-85-NA-GHS-US		

Section 11. Toxicological information

Not available.

Mutagenicity

Not available.

Carcinogenicity

Not available.

Classification

Product/ingredient name	OSHA	IARC	NTP
Fumed Amorphous Silica	-	3	-

Reproductive toxicity

Not available.

Teratogenicity

Not available.

Specific target organ toxicity (single exposure)

Name	Category	Route of exposure	Target organs
Light Aliphatic Hydrocarbon Solvent	Category 3	-	Respiratory tract irritation
Propane	Category 3 Category 3	-	Narcotic effects Respiratory tract irritation
Butane	Category 3 Category 3	-	Narcotic effects Respiratory tract irritation
Lt. Aliphatic Hydrocarbon Solvent	Category 3 Category 3	-	Narcotic effects Respiratory tract irritation
Methyl Cyclohexane	Category 3 Category 3	-	Narcotic effects Narcotic effects

Specific target organ toxicity (repeated exposure)

Name	Category	Route of exposure	Target organs
Light Aliphatic Hydrocarbon Solvent	Category 2	-	-
Propane	Category 2	-	-
Butane	Category 2	-	-
Lt. Aliphatic Hydrocarbon Solvent	Category 2	-	-

Aspiration hazard

Name	Result
Light Aliphatic Hydrocarbon Solvent	ASPIRATION HAZARD - Category 1
Propane	ASPIRATION HAZARD - Category 1
Heavy Paraffinic Oil	ASPIRATION HAZARD - Category 1
Butane	ASPIRATION HAZARD - Category 1
Lt. Aliphatic Hydrocarbon Solvent	ASPIRATION HAZARD - Category 1
Methyl Cyclohexane	ASPIRATION HAZARD - Category 1

Information on the likely routes of exposure : Not available.

Potential acute health effects

Section 11. Toxicological information

- Eye contact** : No known significant effects or critical hazards.
- Inhalation** : Can cause central nervous system (CNS) depression. May cause drowsiness or dizziness. May cause respiratory irritation.
- Skin contact** : Causes skin irritation.
- Ingestion** : Can cause central nervous system (CNS) depression. May be fatal if swallowed and enters airways.

Symptoms related to the physical, chemical and toxicological characteristics

- Eye contact** : Adverse symptoms may include the following:
pain or irritation
watering
redness
- Inhalation** : Adverse symptoms may include the following:
respiratory tract irritation
coughing
nausea or vomiting
headache
drowsiness/fatigue
dizziness/vertigo
unconsciousness
- Skin contact** : Adverse symptoms may include the following:
irritation
redness
- Ingestion** : Adverse symptoms may include the following:
nausea or vomiting

Delayed and immediate effects and also chronic effects from short and long term exposure

Short term exposure

- Potential immediate effects** : Not available.
- Potential delayed effects** : Not available.

Long term exposure

- Potential immediate effects** : Not available.
- Potential delayed effects** : Not available.

Potential chronic health effects

Not available.

- General** : May cause damage to organs through prolonged or repeated exposure.
- Carcinogenicity** : No known significant effects or critical hazards.
- Mutagenicity** : No known significant effects or critical hazards.
- Teratogenicity** : No known significant effects or critical hazards.
- Developmental effects** : No known significant effects or critical hazards.
- Fertility effects** : No known significant effects or critical hazards.

Numerical measures of toxicity

Acute toxicity estimates

Route	ATE value
Oral	25472.22 mg/kg

Section 11. Toxicological information

Section 12. Ecological information

Toxicity

Product/ingredient name	Result	Species	Exposure
Lt. Aliphatic Hydrocarbon Solvent Methyl Cyclohexane Copper	Acute LC50 >100000 ppm Fresh water	Fish - Oncorhynchus mykiss	96 hours
	Acute LC50 5800 µg/l Marine water	Fish - Morone saxatilis - Juvenile (Fledgling, Hatchling, Weanling)	96 hours
	Acute EC50 1100 µg/l Fresh water	Aquatic plants - Lemna minor	4 days
	Acute EC50 2.1 µg/l Fresh water	Daphnia - Daphnia longispina - Juvenile (Fledgling, Hatchling, Weanling)	48 hours
	Acute IC50 16 µg/l Fresh water	Algae - Chlorella pyrenoidosa - Exponential growth phase	72 hours
	Acute IC50 5.4 mg/l Marine water	Aquatic plants - Plantae - Exponential growth phase	72 hours
	Acute LC50 0.072 µg/l Marine water	Crustaceans - Amphipoda - Adult	48 hours
	Acute LC50 7.56 µg/l Marine water	Fish - Periophthalmus waltoni - Adult	96 hours
	Chronic NOEC 2.5 µg/l Marine water	Algae - Nitzschia closterium - Exponential growth phase	72 hours
	Chronic NOEC 7 mg/l Fresh water	Aquatic plants - Ceratophyllum demersum	3 days
Chronic NOEC 0.02 mg/l Fresh water	Crustaceans - Cambarus bartonii - Mature	21 days	
Chronic NOEC 2 µg/l Fresh water	Daphnia - Daphnia magna	21 days	
Chronic NOEC 0.8 µg/l Fresh water	Fish - Oreochromis niloticus - Juvenile (Fledgling, Hatchling, Weanling)	6 weeks	

Persistence and degradability

Not available.

Bioaccumulative potential

Product/ingredient name	LogP _{ow}	BCF	Potential
Light Aliphatic Hydrocarbon Solvent	-	10 to 2500	high
Lt. Aliphatic Hydrocarbon Solvent	-	10 to 2500	high
Methyl Cyclohexane	-	186.21	low

Mobility in soil






Soil/water partition coefficient (K_{oc}) : Not available.

Other adverse effects : No known significant effects or critical hazards.

Section 13. Disposal considerations

Disposal methods : The generation of waste should be avoided or minimized wherever possible. Disposal of this product, solutions and any by-products should at all times comply with the requirements of environmental protection and waste disposal legislation and any regional local authority requirements. Dispose of surplus and non-recyclable products via a licensed waste disposal contractor. Waste should not be disposed of untreated to the sewer unless fully compliant with the requirements of all authorities with jurisdiction. Waste packaging should be recycled. Incineration or landfill should only be considered when recycling is not feasible. This material and its container must be disposed of in a safe way. Empty containers or liners may retain some product residues. Do not puncture or incinerate container.

Section 14. Transport information

	DOT Classification	TDG Classification	Mexico Classification	IATA	IMDG
UN number	UN1950	UN1950	UN1950	UN1950	UN1950
UN proper shipping name	AEROSOLS	AEROSOLS	AEROSOLS	AEROSOLS, flammable	AEROSOLS
Transport hazard class(es)	2.1 	2.1 	2.1 	2.1 	2.1 
Packing group	-	-	-	-	-
Environmental hazards	No.	No.	No.	No.	No.
Additional information	- ERG No. 126 Dependent upon container size, this product may ship under the Limited Quantity shipping exception.	Product classified as per the following sections of the Transportation of Dangerous Goods Regulations: 2.13-2.17 (Class 2). ERG No. 126 Dependent upon container size, this product may ship under the Limited Quantity shipping exception.	- ERG No. 126 Dependent upon container size, this product may ship under the Limited Quantity shipping exception.	- Dependent upon container size, this product may ship under the Limited Quantity shipping exception.	Emergency schedules F-D, S-U Dependent upon container size, this product may ship under the Limited Quantity shipping exception.

Special precautions for user : Multi-modal shipping descriptions are provided for informational purposes and do not consider container sizes. The presence of a shipping description for a particular mode of transport (sea, air, etc.), does not indicate that the product is packaged suitably for that mode of transport. All packaging must be reviewed for suitability prior to shipment, and compliance with the applicable regulations is the sole responsibility of the person offering the product for transport. People loading and unloading dangerous goods must be trained on all of the risks deriving from the substances and on all actions in case of emergency situations.

Section 14. Transport information

Transport in bulk according to IMO instruments : Not available.

Proper shipping name : Not available.

Section 15. Regulatory information

SARA 313

SARA 313 (40 CFR 372.45) supplier notification can be found on the Environmental Data Sheet.

California Prop. 65

WARNING: This product contains a chemical known to the State of California to cause birth defects or other reproductive harm.

International regulations

International lists :

- Australia inventory (AIIIC):** Not determined.
- China inventory (IECSC):** Not determined.
- Japan inventory (CSCL):** Not determined.
- Japan inventory (ISHL):** Not determined.
- Korea inventory (KECI):** Not determined.
- New Zealand Inventory of Chemicals (NZIoC):** Not determined.
- Philippines inventory (PICCS):** Not determined.
- Taiwan Chemical Substances Inventory (TCSI):** Not determined.
- Thailand inventory:** Not determined.
- Turkey inventory:** Not determined.
- Vietnam inventory:** Not determined.

Section 16. Other information

Hazardous Material Information System (U.S.A.)

Health	*	3
Flammability		4
Physical hazards		3

The customer is responsible for determining the PPE code for this material. For more information on HMIS® Personal Protective Equipment (PPE) codes, consult the HMIS® Implementation Manual.

Caution: HMIS® ratings are based on a 0-4 rating scale, with 0 representing minimal hazards or risks, and 4 representing significant hazards or risks. Although HMIS® ratings and the associated label are not required on SDSs or products leaving a facility under 29 CFR 1910.1200, the preparer may choose to provide them. HMIS® ratings are to be used with a fully implemented HMIS® program. HMIS® is a registered trademark and service mark of the American Coatings Association, Inc.

Procedure used to derive the classification

Classification	Justification
FLAMMABLE AEROSOLS - Category 1	On basis of test data
GASES UNDER PRESSURE - Compressed gas	Calculation method
SKIN CORROSION/IRRITATION - Category 2	Calculation method
SPECIFIC TARGET ORGAN TOXICITY (SINGLE EXPOSURE) (Respiratory tract irritation) - Category 3	Calculation method
SPECIFIC TARGET ORGAN TOXICITY (SINGLE EXPOSURE) (Narcotic effects) - Category 3	Calculation method
SPECIFIC TARGET ORGAN TOXICITY (REPEATED EXPOSURE) - Category 2	Calculation method
ASPIRATION HAZARD - Category 1	Calculation method

History

Date of printing : 9/22/2021

Section 16. Other information

Date of issue/Date of revision	: 9/22/2021
Date of previous issue	: 4/19/2021
Version	: 13.01
Key to abbreviations	: ATE = Acute Toxicity Estimate BCF = Bioconcentration Factor GHS = Globally Harmonized System of Classification and Labelling of Chemicals IATA = International Air Transport Association IBC = Intermediate Bulk Container IMDG = International Maritime Dangerous Goods LogPow = logarithm of the octanol/water partition coefficient MARPOL = International Convention for the Prevention of Pollution From Ships, 1973 as modified by the Protocol of 1978. ("Marpol" = marine pollution) N/A = Not available SGG = Segregation Group UN = United Nations

✔ Indicates information that has changed from previously issued version.

Notice to reader

It is recommended that each customer or recipient of this Safety Data Sheet (SDS) study it carefully and consult resources, as necessary or appropriate, to become aware of and understand the data contained in this SDS and any hazards associated with the product. This information is provided in good faith and believed to be accurate as of the effective date herein. However, no warranty, express or implied, is given. The information presented here applies only to the product as shipped. The addition of any material can change the composition, hazards and risks of the product. Products shall not be repackaged, modified, or tinted except as specifically instructed by the manufacturer, including but not limited to the incorporation of products not specified by the manufacturer, or the use or addition of products in proportions not specified by the manufacturer. Regulatory requirements are subject to change and may differ between various locations and jurisdictions. The customer/buyer/user is responsible to ensure that his activities comply with all country, federal, state, provincial or local laws. The conditions for use of the product are not under the control of the manufacturer; the customer/buyer/user is responsible to determine the conditions necessary for the safe use of this product. The customer/buyer/user should not use the product for any purpose other than the purpose shown in the applicable section of this SDS without first referring to the supplier and obtaining written handling instructions. Due to the proliferation of sources for information such as manufacturer-specific SDS, the manufacturer cannot be responsible for SDSs obtained from any other source.