

11/16

 Close this window

SDS

**Common Name:** LOCTITE SF 790 GASKET REMOVER KNOWN AS LOCTITE CHISEL PAINT STRIPPE, 79040**Manufacturer:** HENKEL**SDS Revision Date:** 8/28/2019**SDS Format:** GHS-US**Item Number(s):** 4KM53**Manufacturer Model Number(s):**

## SDS Table of Contents

Click the desired link below to jump directly to that section in the SDS.

- [1. PRODUCT AND COMPANY IDENTIFICATION](#)
- [2. HAZARDS IDENTIFICATION](#)
- [3. COMPOSITION / INFORMATION ON INGREDIENTS](#)
- [4. FIRST AID MEASURES](#)
- [5. FIRE FIGHTING MEASURES](#)
- [6. ACCIDENTAL RELEASE MEASURES](#)
- [7. HANDLING AND STORAGE](#)
- [8. EXPOSURE CONTROLS / PERSONAL PROTECTION](#)
- [9. PHYSICAL AND CHEMICAL PROPERTIES](#)
- [10. STABILITY AND REACTIVITY](#)
- [11. TOXICOLOGICAL INFORMATION](#)
- [12. ECOLOGICAL INFORMATION](#)
- [13. DISPOSAL CONSIDERATIONS](#)
- [14. TRANSPORT INFORMATION](#)
- [15. REGULATORY INFORMATION](#)
- [16. OTHER INFORMATION](#)

HENKEL

SAFETY DATA SHEET

REVISION NUMBER: 008.0

ISSUE DATE: 08/28/2019

### 1. PRODUCT AND COMPANY IDENTIFICATION



PRODUCT NAME:

LOCTITE SF 790 GASKET REMOVER KNOWN AS LOCTITE (R\*) CHISEL (R\*) PAINT STRIPPE

PRODUCT TYPE/USE: CLEANER

RESTRICTION OF USE: NONE IDENTIFIED

IDH NUMBER: 135544

ITEM NUMBER: 79040

REGION: UNITED STATES

COMPANY ADDRESS:  
 HENKEL CORPORATION  
 ONE HENKEL WAY  
 ROCKY HILL, CONNECTICUT 06067

CONTACT INFORMATION:  
 TELEPHONE: +1 (860) 571-5100

MEDICAL EMERGENCY PHONE:  
 POISON CONTROL CENTER: 1-877-671-4608 (TOLL FREE) OR 1-303-592-1711

TRANSPORT EMERGENCY PHONE:  
 CHEMTREC: 1-800-424-9300 (TOLL FREE) OR 1-703-527-3887

INTERNET: WWW.HENKELNA.COM

THIS PRODUCT IS NOT AND CANNOT BE DISTRIBUTED IN COMMERCE (AS DEFINED IN TSCA SECTION 3(5)) OR PROCESSED (AS DEFINED IN TSCA SECTION 3(13)) FOR CONSUMER PAINT OR COATING REMOVAL. PLEASE CONTACT HENKEL PRODUCT SAFETY & REGULATORY AFFAIRS FOR FURTHER INFORMATION.

## 2. HAZARDS IDENTIFICATION



### EMERGENCY OVERVIEW:

DANGER:  
 CONTENTS UNDER PRESSURE.  
 EXTREMELY FLAMMABLE AEROSOL.  
 MAY BE FATAL IF SWALLOWED AND ENTERS AIRWAYS.  
 CAUSES SKIN IRRITATION.  
 CAUSES SERIOUS EYE IRRITATION.  
 MAY CAUSE DROWSINESS OR DIZZINESS.  
 SUSPECTED OF CAUSING CANCER.  
 CAUSES DAMAGE TO ORGANS.  
 MAY CAUSE DAMAGE TO ORGANS THROUGH PROLONGED OR REPEATED EXPOSURE.

HAZARD CLASS	HAZARD CATEGORY
FLAMMABLE AEROSOL.	1
SKIN IRRITATION	2
EYE IRRITATION	2A
CARCINOGENICITY	2
SPECIFIC TARGET ORGAN TOXICITY - SINGLE EXPOSURE	1
SPECIFIC TARGET ORGAN TOXICITY - SINGLE EXPOSURE	3
SPECIFIC TARGET ORGAN TOXICITY - REPEATED EXPOSURE	2
ASPIRATION HAZARD	1

PICTOGRAM(S):  
 FLAME  
 HEALTH HAZARD  
 EXCLAMATION MARK

### PRECAUTIONARY STATEMENTS:

PREVENTION:  
 OBTAIN SPECIAL INSTRUCTIONS BEFORE USE. DO NOT HANDLE UNTIL ALL SAFETY PRECAUTIONS HAVE BEEN READ AND UNDERSTOOD. KEEP AWAY FROM HEAT, SPARKS, OPEN FLAMES, HOT SURFACES - NO SMOKING. DO NOT SPRAY ON AN OPEN FLAME OR

OTHER IGNITION SOURCE. DO NOT PIERCE OR BURN, EVEN AFTER USE. DO NOT BREATHE MIST OR SPRAY. WASH AFFECTED AREA THOROUGHLY AFTER HANDLING. DO NOT EAT, DRINK OR SMOKE WHEN USING THIS PRODUCT. USE ONLY OUTDOORS OR IN A WELL-VENTILATED AREA. WEAR PROTECTIVE GLOVES, CLOTHING, EYE AND FACE PROTECTION.

**RESPONSE:**

IF SWALLOWED: IMMEDIATELY CALL A PHYSICIAN OR POISON CONTROL CENTER.

**IF ON SKIN:**

WASH WITH PLENTY OF WATER. IF INHALED: REMOVE VICTIM TO FRESH AIR AND KEEP AT REST IN A POSITION COMFORTABLE FOR BREATHING. CALL A POISON CENTER OR PHYSICIAN IF YOU FEEL UNWELL.

**IF IN EYES:**

RINSE CAUTIOUSLY WITH WATER FOR SEVERAL MINUTES. REMOVE CONTACT LENSES, IF PRESENT AND EASY TO DO. CONTINUE RINSING.

IF EXPOSED: CALL A POISON CENTER OR PHYSICIAN. DO NOT INDUCE VOMITING.

IF SKIN IRRITATION OCCURS: GET MEDICAL ATTENTION.

**IF EYE IRRITATION PERSISTS:**

GET MEDICAL ATTENTION. TAKE OFF CONTAMINATED CLOTHING.

**STORAGE:**

STORE IN A WELL-VENTILATED PLACE. KEEP CONTAINER TIGHTLY CLOSED. STORE LOCKED UP. PROTECT FROM SUNLIGHT. DO NOT EXPOSE TO TEMPERATURES EXCEEDING 50 DEG. C/122 DEG. F.

**DISPOSAL:**

DISPOSE OF CONTENTS AND/OR CONTAINER ACCORDING TO FEDERAL, STATE/PROVINCIAL AND LOCAL GOVERNMENTAL REGULATIONS.

2% OF THE MIXTURE CONSISTS OF INGREDIENT(S) OF UNKNOWN ACUTE TOXICITY.

CLASSIFICATION COMPLIES WITH OSHA HAZARD COMMUNICATION STANDARD (29 CFR 1910.1200) AND IS CONSISTENT WITH THE PROVISIONS OF THE UNITED NATIONS GLOBALLY HARMONIZED SYSTEM OF CLASSIFICATION AND LABELING OF CHEMICALS (GHS).

SEE SECTION 11 FOR ADDITIONAL TOXICOLOGICAL INFORMATION.

### 3. COMPOSITION / INFORMATION ON INGREDIENTS

 top

HAZARDOUS COMPONENT(S)	CAS NUMBER	PERCENTAGE*
METHYLENE CHLORIDE	75-09-2	60 - 80
PROPANE/ISOBUTANE	68476-86-8	10 - 30
METHANOL	67-56-1	5 - 10

\* EXACT PERCENTAGES MAY VARY OR ARE TRADE SECRET. CONCENTRATION RANGE IS PROVIDED TO ASSIST USERS IN PROVIDING APPROPRIATE PROTECTIONS.

### 4. FIRST AID MEASURES

 top

**INHALATION:**

MOVE TO FRESH AIR. IF NOT BREATHING, GIVE ARTIFICIAL RESPIRATION. IF BREATHING IS DIFFICULT, GIVE OXYGEN. IF SYMPTOMS DEVELOP AND PERSIST, GET MEDICAL ATTENTION.

**SKIN CONTACT:**

IMMEDIATELY FLUSH SKIN WITH PLENTY OF WATER (USING SOAP, IF AVAILABLE).  
IF SYMPTOMS DEVELOP AND PERSIST, GET MEDICAL ATTENTION.

**EYE CONTACT:**

IMMEDIATELY FLUSH EYES WITH PLENTY OF WATER FOR AT LEAST 15 MINUTES. SEEK  
MEDICAL ADVICE.

**INGESTION:**

DO NOT INDUCE VOMITING. NEVER GIVE ANYTHING BY MOUTH TO AN UNCONSCIOUS  
PERSON. IF VOMITING OCCURS, PREVENT ASPIRATION BY KEEPING THE PATIENT'S  
HEAD BELOW THE KNEES. CALL A PHYSICIAN IMMEDIATELY.

SYMPTOMS: SEE SECTION 11.

**5. FIRE FIGHTING MEASURES**

EXTINGUISHING MEDIA: FOAM, DRY CHEMICAL OR CARBON DIOXIDE.

**SPECIAL FIREFIGHTING PROCEDURES:**

FIREFIGHTERS SHOULD WEAR SELF-CONTAINED BREATHING APPARATUS. WATER MAY BE  
INEFFECTIVE, BUT MAY BE USED TO COOL EXPOSED CONTAINERS TO PREVENT PRESSURE  
BUILD-UP AND POSSIBLE AUTO-IGNITION OR EXPLOSION WHEN EXPOSED TO EXTREME  
HEAT. IF WATER IS USED, FOG NOZZLES ARE PREFERABLE.

**UNUSUAL FIRE OR EXPLOSION HAZARDS:**

VAPOURS MAY ACCUMULATE IN LOW OR CONFINED AREAS, TRAVEL CONSIDERABLE  
DISTANCE TO SOURCE OF IGNITION, AND FLASH BACK. CLOSED CONTAINERS MAY  
RUPTURE (DUE TO BUILD UP OF PRESSURE) WHEN EXPOSED TO EXTREME HEAT.

**HAZARDOUS COMBUSTION PRODUCTS:**

IRRITATING ORGANIC VAPOURS. PHOSGENE. HYDROGEN CHLORIDE. OXIDES OF CARBON.

**6. ACCIDENTAL RELEASE MEASURES**

USE PERSONAL PROTECTION RECOMMENDED IN SECTION 8, ISOLATE THE HAZARD AREA  
AND DENY ENTRY TO UNNECESSARY AND UNPROTECTED PERSONNEL.

ENVIRONMENTAL PRECAUTIONS: DO NOT ALLOW TO ENTER THE GROUND / SOIL.

**CLEAN-UP METHODS:**

REMOVE ALL SOURCES OF IGNITION. SPILLED LIQUID IS COMBUSTIBLE AND CAN BE  
IGNITED BY HEAT, FLAMES, SPARKS, OR OTHER SOURCES OF IGNITION. STORE IN A  
CLOSED CONTAINER UNTIL READY FOR DISPOSAL. SOAK UP WITH INERT ABSORBENT.  
SCRAPE UP SPILLED MATERIAL AND PLACE IN A CLOSED CONTAINER FOR DISPOSAL.  
FOR SMALL SPILLS WIPE UP WITH PAPER TOWEL AND PLACE IN CONTAINER FOR  
DISPOSAL.

**7. HANDLING AND STORAGE****HANDLING:**

USE ONLY WITH ADEQUATE VENTILATION. PREVENT CONTACT WITH EYES, SKIN AND  
CLOTHING. DO NOT BREATHE VAPOR AND MIST. WASH THOROUGHLY AFTER HANDLING.  
AVOID BREATHING MISTS OR AEROSOLS OF THIS PRODUCT.

**STORAGE:**

FOR SAFE STORAGE, STORE BETWEEN 0 DEG. C (32 DEG. F) AND 32 DEG. C  
(89.6 DEG. F)

STORE IN A COOL, DRY, WELL-VENTILATED AREA. STORE IN ORIGINAL CONTAINER  
UNTIL READY TO USE.

**8. EXPOSURE CONTROLS / PERSONAL PROTECTION**

EMPLOYERS SHOULD COMPLETE AN ASSESSMENT OF ALL WORKPLACES TO DETERMINE THE NEED FOR, AND SELECTION OF, PROPER EXPOSURE CONTROLS AND PROTECTIVE EQUIPMENT FOR EACH TASK PERFORMED.

HAZARDOUS COMPONENT(S)	ACGIH TLV	OSHA PEL	AIHA WEEL	OTHER
METHYLENE CHLORIDE	50 PPM TWA	12.5 PPM OSHA_ACT 25 PPM TWA 125 PPM STEL	NONE	NONE
PROPANE/ISOBUTANE	NONE	NONE	NONE	NONE
METHANOL	200 PPM TWA (SKIN) 250 PPM STEL	200 PPM (260 MG/M3) PEL	NONE	NONE

**ENGINEERING CONTROLS:**

PROVIDE ADEQUATE LOCAL EXHAUST VENTILATION TO MAINTAIN WORKER EXPOSURE BELOW EXPOSURE LIMITS.

**RESPIRATORY PROTECTION:**

USE NIOSH APPROVED RESPIRATOR IF THERE IS POTENTIAL TO EXCEED EXPOSURE LIMIT(S). USE ONLY IN WELL-VENTILATED AREAS.

**EYE/FACE PROTECTION:**

SAFETY GOGGLES OR SAFETY GLASSES WITH SIDE SHIELDS. FULL FACE PROTECTION SHOULD BE USED IF THE POTENTIAL FOR SPLASHING OR SPRAYING OF PRODUCT EXISTS. SAFETY SHOWERS AND EYE WASH STATIONS SHOULD BE AVAILABLE.

**SKIN PROTECTION:**

USE CHEMICAL RESISTANT, IMPERMEABLE CLOTHING INCLUDING GLOVES AND EITHER AN APRON OR BODY SUIT TO PREVENT SKIN CONTACT. SILVER SHIELD GLOVES. VITON GLOVES. POLYVINYL ALCOHOL GLOVES. 4H GLOVES. EVAL-LAMINATE GLOVES.

**9. PHYSICAL AND CHEMICAL PROPERTIES**

PHYSICAL STATE: AEROSOL, LIQUID

COLOR: GRAY, TO, OFF WHITE

ODOR: SHARP, SOLVENT

ODOR THRESHOLD: NOT AVAILABLE.

PH: NOT AVAILABLE.

VAPOR PRESSURE: NOT AVAILABLE.

BOILING POINT/RANGE: NOT AVAILABLE.

MELTING POINT/RANGE: NOT AVAILABLE.

SPECIFIC GRAVITY: 0.789

VAPOR DENSITY: NOT AVAILABLE.

FLASH POINT: <5 DEG. C (<41 DEG. F)

FLAMMABLE/EXPLOSIVE LIMITS - LOWER: NOT AVAILABLE.

FLAMMABLE/EXPLOSIVE LIMITS - UPPER: NOT AVAILABLE.

AUTOIGNITION TEMPERATURE: NOT AVAILABLE.  
 FLAMMABILITY: EXTREMELY FLAMMABLE AEROSOL.  
 EVAPORATION RATE: NOT AVAILABLE.  
 SOLUBILITY IN WATER: SLIGHTLY SOLUBLE  
 PARTITION COEFFICIENT (N-OCTANOL/WATER): NOT AVAILABLE.  
 VOC CONTENT: 30%; 237 G/L  
 VISCOSITY: NOT AVAILABLE.  
 DECOMPOSITION TEMPERATURE: NOT AVAILABLE.

## 10. STABILITY AND REACTIVITY

 top

STABILITY: STABLE UNDER NORMAL CONDITIONS OF STORAGE AND USE.  
 HAZARDOUS REACTIONS: WILL NOT OCCUR.  
 HAZARDOUS DECOMPOSITION PRODUCTS:  
 HYDROGEN CHLORIDE. OXIDES OF CARBON. IRRITATING ORGANIC VAPOURS. PHOSGENE.  
 INCOMPATIBLE MATERIALS:  
 ACIDS AND BASES. OXIDIZING AGENTS. SODIUM. POTASSIUM.  
 REACTIVITY: NOT AVAILABLE.  
 CONDITIONS TO AVOID: KEEP AWAY FROM HEAT, SPARK AND FLAME.

## 11. TOXICOLOGICAL INFORMATION

 top

RELEVANT ROUTES OF EXPOSURE: SKIN, INHALATION, EYES, INGESTION  
 POTENTIAL HEALTH EFFECTS/SYMPTOMS:  
 INHALATION:  
 INHALATION OF VAPOR OR AEROSOL MAY CAUSE SEVERE IRRITATION TO NOSE,  
 THROAT AND LUNGS. EXCESSIVE INHALATION OF THIS MATERIAL CAUSES HEADACHE,  
 DIZZINESS, NAUSEA AND INCOORDINATION.  
 SKIN CONTACT:  
 CAUSES SKIN IRRITATION. MAY CAUSE IRRITATION DUE TO DEFATTING OF THE SKIN.  
 EYE CONTACT: CAUSES SERIOUS EYE IRRITATION.  
 INGESTION:  
 ASPIRATED MATERIAL CAN ENTER LUNGS AND CAUSE DAMAGE. MAY CAUSE DIZZINESS,  
 INCOORDINATION, HEADACHE, NAUSEA, AND VOMITING.

HAZARDOUS COMPONENT(S)	LD50S AND LC50S	IMMEDIATE AND DELAYED HEALTH EFFECTS
METHYLENE CHLORIDE	ORAL LD50 (RAT): 1,600 MG/KG	BLOOD, CARDIAC, CENTRAL NERVOUS SYSTEM, CORROSIVE, IRRITANT, KIDNEY, LIVER, SOME EVIDENCE OF CARCINOGENICITY
PROPANE/ISOBUTANE	NONE	NO RECORDS

METHANOL	ORAL LD50 (RAT): 5,628 MG/KG	EYES, IRRITANT, METABOLIC, NERVOUS SYSTEM	
	ORAL LD50 (MOUSE): 7,300 MG/KG		
	ORAL LD50 (RABBIT): 14.4 G/KG		
	DERMAL LD50 (RABBIT): 15,800 MG/KG		
HAZARDOUS COMPONENT(S)	NTP CARCINOGEN	IARC CARCINOGEN	OSHA CARCINOGEN (SPECIFICALLY REGULATED)
METHYLENE CHLORIDE	REASONABLY ANTICIPATED TO BE A HUMAN CARCINOGEN.	GROUP 2A	YES
PROPANE/ISOBUTANE	NO	NO	NO
METHANOL	NO	NO	NO

## 12. ECOLOGICAL INFORMATION



ECOLOGICAL INFORMATION: NOT AVAILABLE.

## 13. DISPOSAL CONSIDERATIONS



INFORMATION PROVIDED IS FOR UNUSED PRODUCT ONLY.

RECOMMENDED METHOD OF DISPOSAL:  
FOLLOW ALL LOCAL, STATE, FEDERAL AND PROVINCIAL REGULATIONS FOR DISPOSAL.

HAZARDOUS WASTE NUMBER:  
D001: IGNITABLE.

## 14. TRANSPORT INFORMATION



THE TRANSPORT INFORMATION PROVIDED IN THIS SECTION ONLY APPLIES TO THE MATERIAL/FORMULATION ITSELF, AND IS NOT SPECIFIC TO ANY PACKAGE/CONFIGURATION.

U.S. DEPARTMENT OF TRANSPORTATION GROUND (49 CFR):  
PROPER SHIPPING NAME: AEROSOLS  
HAZARD CLASS OR DIVISION: 2.1  
IDENTIFICATION NUMBER: UN 1950  
PACKING GROUP: NONE

INTERNATIONAL AIR TRANSPORTATION (ICAO/IATA):

PROPER SHIPPING NAME:  
AEROSOLS, FLAMMABLE, CONTAINING SUBSTANCES IN DIVISION 6.1, PACKING  
GROUP III

HAZARD CLASS OR DIVISION: 2.1 (6.1)

IDENTIFICATION NUMBER: UN 1950

PACKING GROUP: NONE

WATER TRANSPORTATION (IMO/IMDG):  
PROPER SHIPPING NAME: AEROSOLS (METHYLENE CHLORIDE)  
HAZARD CLASS OR DIVISION: 2.1 (6.1)  
IDENTIFICATION NUMBER: UN 1950  
PACKING GROUP: NONE

## 15. REGULATORY INFORMATION

 top

UNITED STATES REGULATORY INFORMATION:

TSCA 8(B) INVENTORY STATUS:  
ALL COMPONENTS ARE LISTED OR ARE EXEMPT FROM LISTING ON THE TOXIC  
SUBSTANCES CONTROL ACT INVENTORY.

TSCA 6 RISK MANAGEMENT RULES:  
THIS PRODUCT IS NOT AND CANNOT BE DISTRIBUTED IN COMMERCE (AS DEFINED IN  
TSCA SECTION 3(5)) OR PROCESSED (AS DEFINED IN TSCA SECTION 3(13)) FOR  
CONSUMER PAINT OR COATING REMOVAL. PLEASE CONTACT HENKEL PRODUCT  
SAFETY & REGULATORY AFFAIRS FOR FURTHER INFORMATION.

TSCA 12(B) EXPORT NOTIFICATION: METHYLENE CHLORIDE (CAS# 75-09-2).

CERCLA/SARA SECTION 302 EHS: NONE ABOVE REPORTING DE MINIMIS.

CERCLA/SARA SECTION 311/312:  
FIRE, PRESSURE, IMMEDIATE HEALTH, DELAYED HEALTH

CERCLA/SARA SECTION 313:  
THIS PRODUCT CONTAINS THE FOLLOWING TOXIC CHEMICALS SUBJECT TO THE  
REPORTING REQUIREMENTS OF SECTION 313 OF THE EMERGENCY PLANNING AND  
COMMUNITY RIGHT-TO-KNOW ACT OF 1986 (40 CFR 372).  
METHANOL (CAS# 67-56-1).  
METHYLENE CHLORIDE (CAS# 75-09-2).

CERCLA REPORTABLE QUANTITY:  
METHYLENE CHLORIDE (CAS# 75-09-2) 1,000 LBS. (454 KG)

CALIFORNIA PROPOSITION 65:  
THIS PRODUCT CONTAINS A CHEMICAL KNOWN IN THE STATE OF CALIFORNIA TO CAUSE  
CANCER. THIS PRODUCT CONTAINS A CHEMICAL KNOWN TO THE STATE OF CALIFORNIA  
TO CAUSE BIRTH DEFECTS OR OTHER REPRODUCTIVE HARM.

CANADA REGULATORY INFORMATION:

CEPA DSL/NDSL STATUS:  
ALL COMPONENTS ARE LISTED ON OR ARE EXEMPT FROM LISTING ON THE CANADIAN  
DOMESTIC SUBSTANCES LIST.

## 16. OTHER INFORMATION

 top

THIS SAFETY DATA SHEET CONTAINS CHANGES FROM THE PREVIOUS VERSION IN  
SECTIONS: 1, 15

PREPARED BY: PRODUCT SAFETY AND REGULATORY AFFAIRS

ISSUE DATE: 08/28/2019

DISCLAIMER:  
THE DATA CONTAINED HEREIN ARE FURNISHED FOR INFORMATION ONLY AND ARE  
BELIEVED TO BE RELIABLE. HOWEVER, HENKEL CORPORATION AND ITS AFFILIATES

('HENKEL') DOES NOT ASSUME RESPONSIBILITY FOR ANY RESULTS OBTAINED BY PERSONS OVER WHOSE METHODS HENKEL HAS NO CONTROL. IT IS THE USER'S RESPONSIBILITY TO DETERMINE THE SUITABILITY OF HENKEL'S PRODUCTS OR ANY PRODUCTION METHODS MENTIONED HEREIN FOR A PARTICULAR PURPOSE, AND TO ADOPT SUCH PRECAUTIONS AS MAY BE ADVISABLE FOR THE PROTECTION OF PROPERTY AND PERSONS AGAINST ANY HAZARDS THAT MAY BE INVOLVED IN THE HANDLING AND USE OF ANY HENKEL'S PRODUCTS. IN LIGHT OF THE FOREGOING, HENKEL SPECIFICALLY DISCLAIMS ALL WARRANTIES, EXPRESS OR IMPLIED, INCLUDING WARRANTIES OF MERCHANTABILITY AND FITNESS FOR A PARTICULAR PURPOSE, ARISING FROM SALE OR USE OF HENKEL'S PRODUCTS. HENKEL FURTHER DISCLAIMS ANY LIABILITY FOR CONSEQUENTIAL OR INCIDENTAL DAMAGES OF ANY KIND, INCLUDING LOST PROFITS.

THIS SAFETY DATA SHEET HAS BEEN GENERATED BASED ON OSHA HAZARD COMMUNICATION STANDARD (29 CFR 1910.1200) AND PROVIDES INFORMATION IN ACCORDANCE WITH U.S. FEDERAL LAW ONLY. NO WARRANTY OR REPRESENTATION OF ANY KIND IS GIVEN WITH RESPECT TO THE SUBSTANTIVE OR EXPORT LAWS OF ANY OTHER JURISDICTION OR COUNTRY. PLEASE CONFIRM THAT THE INFORMATION PROVIDED HEREIN CONFORMS TO THE SUBSTANTIVE EXPORT OR OTHER LAW OF ANY OTHER JURISDICTION PRIOR TO EXPORT. PLEASE CONTACT HENKEL PRODUCT SAFETY AND REGULATORY AFFAIRS FOR ADDITIONAL ASSISTANCE.